

# Gear Operated Grooved B/Fly Valve Without Tampered Switch

## GEAR OPERATED GROOVED B/FLY VALVE WITHOUT TAMPERED SWITCH



### STANDARD SPECIFICATIONS:

<b>BODY MATERIAL</b>	<b>: DUCTILE IRON</b>
<b>WORKING PRESSURE</b>	<b>: 300 PSI</b>
<b>TEMPERATURE RANGE</b>	<b>: 0° C TO 80° C</b>
<b>SIZE RANGE</b>	<b>: DN50 TO DN200</b>
<b>END CONNECTION</b>	<b>: GROOVED TO AWWA C606</b>
<b>COATING</b>	<b>: FUSION BONDED EPOXY</b>
<b>APPROVALS</b>	<b>: UL &amp; FM &amp; AS 4020</b>



**WATERMARKED**

### ORDERING INFORMATION:

Part No.	Description
050GORGBV	50mm Gear Operated Grooved B/Fly Valve
065GORGBV	65mm Gear Operated Grooved B/Fly Valve
080GORGBV	80mm Gear Operated Grooved B/Fly Valve
100GORGBV	100mm Gear Operated Grooved B/Fly Valve
125GORGBV	125mm Gear Operated Grooved B/Fly Valve
150GORGBV	150mm Gear Operated Grooved B/Fly Valve
200GORGBV	200mm Gear Operated Grooved B/Fly Valve

### TECHNICAL INFORMATION:

DN		DIMENSIONS IN mm	
Inch	mm	END TO END	OD
2	50	81	60.3
2.5	65	97	76.1
3	80	97	88.9
4	100	116	114.3
5	125	148	141.3
6	150	148	165.1
8	200	133	219.1

**Fire Australia Co Pty Ltd.**

ABN No. 13165523713

5/47, Rushdale St. Knoxfield VIC-3180

Tel:(03) 9764 0020, Fax: 9764 0023. E-mail: [sales@fireausco.com.au](mailto:sales@fireausco.com.au)

FA-HV/06/16