

NRS FLANGED & GROOVED RESILIENT GATE VALVE**STANDARD SPECIFICATIONS:**

BODY MATERIAL	: DUCTILE IRON
WORKING PRESSURE	: 300 PSI
TEMPERATURE RANGE	: 0° C TO 80° C
SIZE RANGE	: DN50 TO DN200
END CONNECTION	: FLANGES DRILLED TO AS 2129 TABLE-E & GROOVED TO AWWA C606
COATING	: FUSION BONDED EPOXY
APPROVALS	: UL & FM

ORDERING INFORMATION:

Part No.	Description
050NRSFLRGGV	50mm NRS Flanged & Grooved Resilient Gate Valve
065NRSFLRGGV	65mm NRS Flanged & Grooved Resilient Gate Valve
080NRSFLRGGV	80mm NRS Flanged & Grooved Resilient Gate Valve
100NRSFLRGGV	100mm NRS Flanged & Grooved Resilient Gate Valve
125NRSFLRGGV	125mm NRS Flanged & Grooved Resilient Gate Valve
150NRSFLRGGV	150mm NRS Flanged & Grooved Resilient Gate Valve
200NRSFLRGGV	200mm NRS Flanged & Grooved Resilient Gate Valve

TECHNICAL INFORMATION:

DN		DIMENSIONS IN mm				
Inch	mm	END TO END	GROOVE OD	FLANGE PCD	No. of Flange HOLES	HOLE Ø
2	50	178	60.3	114	4	18
2.5	65	190	76.1	127	4	18
3	80	203	88.9	146	4	18
4	100	229	114.3	178	8	18
5	125	254	141.3	210	8	18
6	150	267	165.1	235	8	22
8	200	292	219.1	292	8	22