

NRS FLANGED RESILIENT GATE VALVE**STANDARD SPECIFICATIONS:**

BODY MATERIAL	: DUCTILE IRON
WORKING PRESSURE	: 300 PSI
TEMPERATURE RANGE	: 0° C TO 80° C
SIZE RANGE	: DN50 TO DN200
END CONNECTION	: FLANGES DRILLED TO AS2129 TABLE-E
COATING	: FUSION BONDED EPOXY
APPROVALS	: UL & FM

ORDERING INFORMATION:

Part No.	Description
050NRSFLGV	50mm NRS Flanged Resilient Gate Valve
065NRSFLGV	65mm NRS Flanged Resilient Gate Valve
080NRSFLGV	80mm NRS Flanged Resilient Gate Valve
100NRSFLGV	100mm NRS Flanged Resilient Gate Valve
125NRSFLGV	125mm NRS Flanged Resilient Gate Valve
150NRSFLGV	150mm NRS Flanged Resilient Gate Valve
200NRSFLGV	200mm NRS Flanged Resilient Gate Valve

TECHNICAL INFORMATION:

DN		DIMENSIONS IN mm				
Inch	mm	END TO END	HEIGHT From Body Centre to Top	PCD	No. Of Holes	HOLE Ø
2	50	178	278	114	4	18
2.5	65	190	300	127	4	18
3	80	203	321	146	4	18
4	100	229	375	178	8	18
5	125	254	415	210	8	18
6	150	267	455	235	8	22
8	200	292	565	292	8	22