

NRS GROOVED RESILIENT GATE VALVE**STANDARD SPECIFICATIONS:**

BODY MATERIAL	: DUCTILE IRON
WORKING PRESSURE	: 300 PSI
TEMPERATURE RANGE	: 0° C TO 80° C
SIZE RANGE	: DN50 TO DN200
END CONNECTION	: GROOVED TO AWWA C606
COATING	: FUSION BONDED EPOXY
APPROVALS	: UL & FM

ORDERING INFORMATION:

Part No.	Description
050NRSRGGV	50mm NRS Grooved Resilient Gate Valve
065NRSRGGV	65mm NRS Grooved Resilient Gate Valve
080NRSRGGV	80mm NRS Grooved Resilient Gate Valve
100NRSRGGV	100mm NRS Grooved Resilient Gate Valve
125NRSRGGV	125mm NRS Grooved Resilient Gate Valve
150NRSRGGV	150mm NRS Grooved Resilient Gate Valve
200NRSRGGV	200mm NRS Grooved Resilient Gate Valve

TECHNICAL INFORMATION:

DN		DIMENSIONS IN mm		
Inch	mm	END TO END	HEIGHT From Body Centre to Top	OD
2	50	178	254	60.3
2.5	65	190	275	76.1
3	80	203	301	88.9
4	100	229	355	114.3
5	125	254	393	141.3
6	150	267	448	165.1
8	200	292	548	219.1