

OS & Y GROOVED RESILIENT GATE VALVE

STANDARD SPECIFICATIONS:

BODY MATERIAL	: DUCTILE IRON
WORKING PRESSURE	: 300 PSI
TEMPERATURE RANGE	: 0° C TO 80° C
SIZE RANGE	: DN50 TO DN200
END CONNECTION	: GROOVED TO AWWA C606
COATING	: FUSION BONDED EPOXY
APPROVALS	: UL & FM

ORDERING INFORMATION:

Part No.	Description
050OSYRGGV	50mm OS&Y Grooved Resilient Gate Valve
065OSYRGGV	65mm OS&Y Grooved Resilient Gate Valve
080OSYRGGV	80mm OS&Y Grooved Resilient Gate Valve
100OSYRGGV	100mm OS&Y Grooved Resilient Gate Valve
125OSYRGGV	125mm OS&Y Grooved Resilient Gate Valve
150OSYRGGV	150mm OS&Y Grooved Resilient Gate Valve
200OSYRGGV	200mm OS&Y Grooved Resilient Gate Valve
MONITORED VALVES	
050MOSYRGGV	50mm Monitored OS&Y Grooved Resilient Gate Valve
065MOSYRGGV	65mm Monitored OS&Y Grooved Resilient Gate Valve
080MOSYRGGV	80mm Monitored OS&Y Grooved Resilient Gate Valve
100MOSYRGGV	100mm Monitored OS&Y Grooved Resilient Gate Valve
125MOSYRGGV	125mm Monitored OS&Y Grooved Resilient Gate Valve
150MOSYRGGV	150mm Monitored OS&Y Grooved Resilient Gate Valve
200MOSYRGGV	200mm Monitored OS&Y Grooved Resilient Gate Valve

TECHNICAL INFORMATION:

DN		DIMENSIONS IN mm			
Inch	mm	END TO END	WHEN CLOSE From Body Centre to Top	WHEN OPEN From Body Centre to Top	OD
2	50	178	348	400	60.3
2.5	65	190	373	440	76.1
3	80	203	408	490	88.9
4	100	229	471	573	114.3
5	125	254	541	665	141.3
6	150	267	601	755	165.1
8	200	292	774	975	219.1