



PRODUCT CODE

- | | |
|-------------------|--|
| 1] 150QQBFHST | QLD QUAD BOOSTER & FEED HYDRANT GROOVED WITH STORZ |
| 2] 150QQBFHQFBT | QLD QUAD BOOSTER & FEED HYDRANT GROOVED WITH QLD FBT |
| 3] 150QQBFHSTFL | QLD QUAD BOOSTER & FEED HYDRANT FLANGED WITH STORZ |
| 4] 150QQBFHQFBTFL | QLD QUAD BOOSTER & FEED HYDRANT FLANGED WITH QLD FBT |

APPROVALS

- | | |
|---------------------------|---------------------------------|
| 1] Comply to | - AS 2419 |
| 2] Full Flow Check Valve- | UL/FM Approved |
| 3] Butter Fly Valve | - UL/FM Approved & Water Marked |
| 4] Booster Head | - AS 2419.3-2012 & Water Marked |
| 5] Hydrant Valves | - AS 2419.2-2009 & Water Marked |
| 6] Pipe | - Hot Dip Galvanized |
| 7] R/G Couplings | - UL/FM Approved |

WORKING PRESSURE

- | | |
|--------------------------|------------|
| 1] Full Flow Check Valve | - 2068 kPa |
| 2] Butter Fly Valve | - 2068 kPa |
| 3] Booster Head | - 1400 kPa |
| 4] Hydrant Valves | - 1850 kPa |
| 5] R/G Couplings | - 2068 kPa |

AVAILABLE OPTIONS

- | |
|--|
| 1] Butter Fly Valve installed under Booster Head where head pressure is greater than 50 kPa. |
|--|

