

**Brass Hydrant Valves With BSP Inlet - Oblique Outlet**

The Hydrant Valves are also termed as “Millcocks” or “Landing Valves”. The main purpose of the Hydrant Valves is to control the water flow for the fire fighting purposes. The Hydrant Valves are designed with standard connections at inlets & outlets. The Hydrant Valves can be installed either as “Attack Hydrants” that are used to fight the fire directly or as “Feed Hydrants” supplying water that is pumped back into the fire service through the booster heads. The outlet connections are Australian State specific. The Hydrant Valves supplied by Fire Australia Co comply to the Australian Standards.

**STANDARD SPECIFICATIONS:**

<b>BODY MATERIAL</b>	<b>: GUNMETAL</b>
<b>APPROVALS</b>	<b>: AS/NZS 2419.2-2009</b>
<b>TYPE</b>	<b>: OBLIQUE</b>
<b>INLET CONNECTION</b>	<b>: 2.5” BSP(M)</b>
<b>OUTLET CONNECTION</b>	<b>: CFA/STORZ/2.5” BSP (M)/MFB</b>

Part No.	Description
65HVOBBST	65mm BSP Male Hydrant Valve Oblique Brass with Storz outlet
65HVOBBCFA	65mm BSP Male Hydrant Valve Oblique Brass with CFA outlet
65HVOBBBSP	65mm BSP Male Hydrant Valve Oblique Brass with BSP outlet
65HVOBBMFB	65mm BSP Male Hydrant Valve Oblique Brass with MFB outlet

**Approvals: AS/NZS 2419.2-2009**