

**Brass Hydrant Valves With Grooved Inlet - Oblique Outlet**

The Hydrant Valves are also termed as “Millcocks” or “Landing Valves”. The main purpose of the Hydrant Valves is to control the water flow for the fire fighting purposes. The Hydrant Valves are designed with standard connections at inlets & outlets. The Hydrant Valves can be installed either as “Attack Hydrants” that are used to fight the fire directly or as “Feed Hydrants” supplying water that is pumped back into the fire service through the booster heads. The outlet connections are Australian State specific. The Hydrant Valves supplied by Fire Australia Co comply to the Australian Standards.

**STANDARD SPECIFICATIONS:**

- BODY MATERIAL** : GUNMETAL  
**APPROVALS** : AS/NZS 2419.2-2009  
**TYPE** : OBLIQUE  
**INLET CONNECTION** : 80mm ROLL GROOVE  
**OUTLET CONNECTION** : CFA/STORZ/2.5” BSP (M)/MFB

Part No.	Description
80HVOBRGST	80mm Hydrant Valve Oblique Brass Grooved with Storz outlet
80HVOBRGCFA	80mm Hydrant Valve Oblique Brass Grooved with CFA outlet
80HVOBRGBSP	80mm Hydrant Valve Oblique Brass Grooved with BSP outlet
80HVOBRGMFB	80mm Hydrant Valve Oblique Brass Grooved with MFB outlet

**Approvals: AS/NZS 2419.2-2009**