

Brass Hydrant Valves With BSP Inlet - Rt. Angled Outlet

The Hydrant Valves are also termed as “Millcocks” or “Landing Valves”. The main purpose of the Hydrant Valves is to control the water flow for the fire fighting purposes. The Hydrant Valves are designed with standard connections at inlets & outlets. The Hydrant Valves can be installed either as “Attack Hydrants” that are used to fight the fire directly or as “Feed Hydrants” supplying water that is pumped back into the fire service through the booster heads. The outlet connections are Australian State specific. The Hydrant Valves supplied by Fire Australia Co comply to the Australian Standards.

STANDARD SPECIFICATIONS:

BODY MATERIAL	: GUNMETAL
APPROVALS	: AS/NZS 2419.2-2009
TYPE	: RIGHT ANGLED
INLET CONNECTION	: 2.5” BSP(M)
OUTLET CONNECTION	: NSW/STORZ/QRT/SA/2.5” BSP (M)

Part No.	Description
65HVRABBST	65mm BSP Male Hydrant Valve Right Angled Brass with Storz outlet
65HVRABBNSW	65mm BSP Male Hydrant Valve Right Angled Brass with NSW outlet
65HVRABBSP	65mm BSP Male Hydrant Valve Right Angled Brass with BSP outlet
65HVRABBQRT	65mm BSP Male Hydrant Valve Right Angled Brass with QRT outlet
65HVRABBSA	65mm BSP Male Hydrant Valve Right Angled Brass with SA outlet

**Approvals: AS/NZS 2419.2-2009****Fire Australia Co Pty Ltd.**

ABN No. 13165523713

5/47, Rushdale St. Knoxfield VIC-3180

Tel:(03) 9764 0020, Fax: 9764 0023. E-mail: sales@fireausco.com.au

FA-HV/04/17