

**SS Hydrant Valves With BSP Inlet - Oblique Outlet**

The Hydrant Valves are also termed as “Millcocks” or “Landing Valves”. The main purpose of the Hydrant Valves is to control the water flow for the fire fighting purposes. The Hydrant Valves are designed with standard connections at inlets & outlets. The Hydrant Valves can be installed either as “Attack Hydrants” that are used to fight the fire directly or as “Feed Hydrants” supplying water that is pumped back into the fire service through the booster heads. The outlet connections are Australian State specific. The Hydrant Valves supplied by Fire Australia Co comply to the Australian Standards.

**STANDARD SPECIFICATIONS:**

- BODY MATERIAL** : STAINLESS STEEL-304  
**APPROVALS** : AS/NZS 2419.2-2009  
**TYPE** : OBLIQUE  
**INLET CONNECTION** : 2.5” BSP(M)  
**OUTLET CONNECTION** : CFA/STORZ/MFB/2.5” BSP (M)

Part No.	Description
65HVOSSBST	65mm BSP Male Hydrant Valve Oblique Stainless Steel with Storz outlet
65HVOSSBCFA	65mm BSP Male Hydrant Valve Oblique Stainless Steel with CFA outlet
65HVOSSBSP	65mm BSP Male Hydrant Valve Oblique Stainless Steel with BSP outlet
65HVOSSBMFB	65mm BSP Male Hydrant Valve Oblique Stainless Steel with MFB outlet

**Approvals: AS/NZS 2419.2-2009****Fire Australia Co Pty Ltd.**

ABN No. 13165523713

5/47, Rushdale St. Knoxfield VIC-3180

Tel:(03) 9764 0020, Fax: 9764 0023. E-mail: [sales@fireausco.com.au](mailto:sales@fireausco.com.au)

FA-HV/04/17