

SS Hydrant Valves With Roll Grooved Inlet - Oblique Outlet

The Hydrant Valves are also termed as “Millcocks” or “Landing Valves”. The main purpose of the Hydrant Valves is to control the water flow for the fire fighting purposes. The Hydrant Valves are designed with standard connections at inlets & outlets. The Hydrant Valves can be installed either as “Attack Hydrants” that are used to fight the fire directly or as “Feed Hydrants” supplying water that is pumped back into the fire service through the booster heads. The outlet connections are Australian State specific. The Hydrant Valves supplied by Fire Australia Co comply to the Australian Standards.

STANDARD SPECIFICATIONS:

- BODY MATERIAL** : STAINLESS STEEL-304
APPROVALS : AS/NZS 2419.2-2009
TYPE : OBLIQUE
INLET CONNECTION : 80mm ROLL GROOVE
OUTLET CONNECTION : CFA/STORZ/MFB/2.5” BSP (M)

Part No.	Description
80HVOSSRGST	80mm Hydrant Valve Oblique Stainless Steel Grooved with Storz outlet
80HVOSSRGCF	80mm Hydrant Valve Oblique Stainless Steel Grooved with CFA outlet
80HVOSSRGBSP	80mm Hydrant Valve Oblique Stainless Steel Grooved with BSP outlet
80HVOSSRGMFB	80mm Hydrant Valve Oblique Stainless Steel Grooved with MFB outlet

**Approvals: AS/NZS 2419.2-2009****Fire Australia Co Pty Ltd.**

ABN No. 13165523713

5/47, Rushdale St. Knoxfield VIC-3180

Tel:(03) 9764 0020, Fax: 9764 0023. E-mail: sales@fireausco.com.au

FA-HV/04/17